

Precision scale

Precision scale with LCD display



PCS



PERCEN



BAT



AC/DC



CAL EXT



NO VERIF

FEATURES:

- Backlight LCD display.
- 6 digits of 23mm.
- ABS housing.
- Stainless steel pan.
- Capacities from 200 g to 6000 g.
- External calibration.
- 5 keys.
- Units: g/ct/oz/ozt/lb/N/dwt/GN/tIT/%.
- Adjustable feet in height.
- Blister included.
- Bubble level.
- Time of answer: 2-3 seconds.
- Operating temperature range: +5°C +35°C
- Alimentation with adaptor AC/DC 100-240Vac 50-60Hz with 12V
- It can be used with 9V batteries (not included).

FUNCTIONS

- Piece counting
- Percentage weight
- Tare



| Code# | Capacity (g) | Readout (g) | Pan dimensions (mm) | Packing dimensions (mm) | Packing weight (kg) | Certifications | |
|--------|--------------|-------------|---------------------|-------------------------|---------------------|----------------|--|
| | | | | | | ENAC | |
| | | | | | | Code # | |
| 261016 | 200 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261017 | 300 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261018 | 500 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261019 | 600 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261020 | 1000 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261021 | 2000 | 0,01 | Ø128 | 300x210x125 | 1,5 | 900039 | |
| 261022 | 3000 | 0,1 | 145x160 | 300x210x125 | 1,5 | 900039 | |
| 261023 | 5000 | 0,1 | 145x160 | 300x210x125 | 1,5 | 900039 | |
| 261024 | 6000 | 0,1 | 145x160 | 300x210x125 | 1,5 | 900001 | |